UNTITLED READING CONE

Bernhard Osann

Family of table, floor and wall LED lamps in extruded matt black painted aluminum with joints for flexible and dynamic positioning of the light.

Available in the version with the linear lighting unit in polymer filled with glass fibers that rotates on itself and in the version with cylindrical spot light in aluminum. Dimmer on board located on the lamp stem.



LED 2700K

LAMPING

Source Total power

Emission Switching Tension

Color temperature Luminous flux Typ cri

Energy class Materials

Notes

Codes

UNT LNN 25

Certificazioni

 ϵ

EAC

LED spot 8W

spot orientable dimmable, on board


110/240V 2700K 550lm 90 A+

aluminum, technopolymer

cable length 2m

Structure/Diffuser

black/gold burnished



LED 3000K

LAMPING

Source Total power

Emission Switching Tension

Color temperature Luminous flux Typ cri

Energy class Materials

Notes

Codes

UNT LNN 26

Certificazioni

 ϵ

EAC

LED spot 8W

spot orientable dimmable, on board


110/240V 3000K 550lm 90 A+

aluminum, technopolymer

cable length 2m

Structure/Diffuser

black/gold burnished



LED 2700K

LAMPING

Source Total power

 ${\sf Emission}$

Switching

Tension
Color temperature
Luminous flux

Typ cri

Energy class

 ${\sf Materials}$

Notes

Codes

UNT LNN 23

Certificazioni

 ϵ

EHC

LED board

7W

orientable


dimmable, on board

110/240V 2700K 485lm 90 A+

aluminum, technopolymer

cable length 2m

Structure



LED 3000K

LAMPING

Source

Total power

 ${\sf Emission}$

Switching

Tension
Color temperature

Luminous flux

Typ cri

Energy class

Materials

Notes

Codes

UNT LNN 24

Certificazioni

 ϵ

EHC

LED board

7W

orientable

dimmable, on board


110/240V 3000K 485lm 90

Д+

aluminum, technopolymer

cable length 2m

Structure



LED 2700K

LAMPING

Source

Total power

Emission Switching

Tension
Color temperature
Luminous flux

Typ cri

Energy class

 ${\sf Materials}$

Notes

Codes

UNT LNN 21

Certificazioni

 ϵ

EHC

LED spot 40°

8W


spot orientable dimmable, on board

110/240V 2700K 550lm 90 A+

aluminum, technopolymer

cable length 2m

Structure



LED 3000K

LAMPING

Source

Total power

Emission Switching

Tension

Color temperature Luminous flux

Typ cri

Energy class

Materials

Notes

Codes

UNT LNN 22

Certificazioni

 ϵ

EHC

LED spot 40°

8W

spot orientable dimmable, on board

110/240V 3000K 550lm 90 A+

aluminum, technopolymer

cable length 2m

Structure

