
PIPISTRELLO-MED


code: 620/MED/DIM/BI




TABLE LAMP, DIFFUSED LIGHT, ADJUSTABLE HEIGHT. GLAZED STAINLESS STEEL TELESCOPE. WHITE OPAL METHACRYLATE DIFFUSER. BASE AND KNOB: DARK BROWN OR WHITE, WITH LED LIGHT SOURCE. DIMMABLE. ELECTRONIC DRIVER ON THE PLUG.

TECHNICAL DRAWINGS







DESIGN GAE AULENTI 1965

UTILIZATION: INTERNAL

TYPOLOGY: **TABLE LAMPS**



WEIGHT NET: -

COLOURS

STRUCTURE: DIFFUSER:

WHITE WHITE

MATERIALS

STRUCTURE: STAINLESS STEEL DIFFUSER:

OPAL WHITE METHACRYLATE

MEASURES WIDTH: -

DIAMETER: 40 cm HEIGHT: 50-62 cm HOLE DIAMETER: -HOLE DEPTH: -

GROSS: -

LENGTH: -

DEPTH: -

PACKAGING VOL.M3: -NUMBER OF ITEMS: 1

BULBS LED 1X9W

FLUX: 850LM KELVIN: 2700° CLASS: A++ CRI: -

COLOR TOLERANCE: -

DURATION: -



DEVICE SPECIFICATIONS

TYPE OF EMISSION: DIFFUSED POWER: 10 W

FLOW LAMP: 787 Im BEAM ANGLE: -

DEVICE EFFICIENCY: 78.7Im/W

IMPACT RESISTENCE: -GLOW WIRE TEST: -

POWER SUPPLY CABLE LENGTH: 35+200cm LENGTH OF HANGING CABLE: -

SUPPLY: INCLUDED

POWER SUPPLY ASSEMBLY: EXTERNAL TYPE OF DIMMING: DIMMER ON CABLE

VOLTAGE: 230 V

POWER SUPPLY: ELECTRONIC DIMMABLE POWER SUPPLY







MARKETS THIS ITEM IS AVAILABLE IN THE FOLLOWING COUNTRIES:

EUROPE



PIPISTRELLO-MED


code: 620/MED/DIM/BI

PHOTO GALLERY











martinelli luce


PIPISTRELLO-MED


code: 620/MED/DIM/MA




TABLE LAMP, DIFFUSED LIGHT, ADJUSTABLE HEIGHT. GLAZED STAINLESS STEEL TELESCOPE. WHITE OPAL METHACRYLATE DIFFUSER. BASE AND KNOB: DARK BROWN OR WHITE, WITH LED LIGHT SOURCE. DIMMABLE. ELECTRONIC DRIVER ON THE PLUG.

TECHNICAL DRAWINGS







DESIGN GAE AULENTI 1965

UTILIZATION: INTERNAL TYPOLOGY: **TABLE LAMPS**

COLOURS STRUCTURE: **DARK BROWN**

DIFFUSER: WHITE

STRUCTURE: STAINLESS STEEL MATERIALS

> DIFFUSER: **OPAL WHITE METHACRYLATE**

MEASURES WIDTH: -DIAMETER: 40 cm WEIGHT NET: -GROSS: -

HEIGHT: 50-62 cm HOLE DIAMETER: -LENGTH: -HOLE DEPTH: -

DEPTH: -

PACKAGING VOL.M3: -NUMBER OF ITEMS: 1

BULBS LED 1X9W

FLUX: 850LM KELVIN: 2700° CLASS: A++ CRI: -

COLOR TOLERANCE: -

DURATION: -



DEVICE SPECIFICATIONS

TYPE OF EMISSION: DIFFUSED POWER: 10 W

FLOW LAMP: 787 Im BEAM ANGLE: -

DEVICE EFFICIENCY: 78.7Im/W

IMPACT RESISTENCE: -

GLOW WIRE TEST: -

POWER SUPPLY ASSEMBLY: EXTERNAL TYPE OF DIMMING: DIMMER ON CABLE

LENGTH OF HANGING CABLE: -

POWER SUPPLY CABLE LENGTH: 35+200cm

VOLTAGE: 230 V

SUPPLY: INCLUDED

POWER SUPPLY: ELECTRONIC DIMMABLE POWER SUPPLY







MARKETS THIS ITEM IS AVAILABLE IN THE FOLLOWING COUNTRIES:

EUROPE



PIPISTRELLO-MED

code: 620/MED/DIM/MA

DESIGN GAE AULENTI 1965

PHOTO GALLERY









