


# FLOS

■ F3150030 Black


## IPNOS OUTDOOR Anodized black

Designed by Nicoletta Rossi and Guido Bianchi, 2014



15W - 3500K - CRI> 85

Floor lamp providing diffused light. Extruded aluminium frame 10x10x1 gratiné and anodized in various finishes. Leds on the top edges incorporated in the extrusions and burnished into the resin, guaranteeing the IP level. ON/OFF switch in the IP box containing the drivers. Two-pole spark-proof schuko plug.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8059607017432
Mounting	Floor
Light Source Type	LED
LED type	LED Module
Power (W)	15

### Physical

Colour	Black
Length (mm)	350
Net weight (kg)	1.15
Package height (mm)	745
Package width (mm)	465
Package length (mm)	465
Package volume (m3)	0.16
IP internal	55

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



Beam Angle: 73°

h(m)	E(lx)	D(m)
1	337	1.49
2	84	2.98
3	37	4.47
4	21	5.96
5	13	7.44

Luminous flux Luminaire  
744 lm

## Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3500
CRI>	85

## Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	No
Dimming type	Electronic 24V
Dimming interface	Switch Integrated (Not Dimmable)
Plug type	Type C
Batteries inside	No
Charging min time	NO

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Accessories & Power Supply



OPTIONAL  
Accessory

F3125000

Ipnos Top Plate