FLOS

Technical Specifications




Skygarden 2

by Marcel Wanders , 2007

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lampholder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injectionmolded PC rose, painted the same color as the body.

Mart Harrison and the second s



Mounting	Pendant
Environment	Indoor
Finish	Glossy white, Glossy black, Matt gold, Matt
	rusty brown
Weight	29,0 Кд
Light sources available	1 x LED 8W E27 1020lm 2700K* [e] cod. RF25026 No dimm.
Emergency	Without
Voltage	220-250V
Power	MAX 230W
Battery	No
Supply included	Yes
Cord Length	4000 mm
Cord Length Materials	4000 mm Glass, Plaster, Stainless steel
-	