


Pendant Luminaires | 220-240 V | 16xE14 **9566**



| Technical data | |
|--|-----------------------|
| Construction year | 2021 |
| Туре | Pendant Luminaires |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Power | 16 x 6 W |
| Lamp cap | 16 x E14 |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Light emission direction | downward and upward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | Swivelling |
| total angle (vertical plane) | 360 ° |
| total angle (horizontal plane) | 60 ° |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| | • |





| Finishing casing | | | | |
|------------------|----------------|--|--|--|
| Material | Brass | | | |
| Colour | gold | | | |
| Processing | Electroplating | | | |

| Finishing diffuser | | | |
|--------------------|-------------------|--|--|
| Material | Iron - Iron | | |
| Processing | Coating - Coating | | |

| Finishing mounting frame | | |
|--------------------------|----------------|--|
| Material | Brass | |
| Colour | gold | |
| Processing | Electroplating | |

Megafono



Pendant Luminaires | 220-240 V | 16xE14 **9566**

Double emission pendant luminaires for indoor application. LED lamplamp included, lamp cap 16xE14.

The device body is made of brass and features a gold finish, processed by means of electroplating; the diffuser is made of iron with a coating treatment; the diffuser is made of iron with a coating treatment; the mounting frame is made of brass, with a gold finish, processed by means of electroplating. The ingress protection degree is IP20;

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

| Illuminotechnical Features | |
|---|----------|
| Source lumens | 12896 lm |
| Colour temperature | 2700 K |
| Junction temperature (lighting fixture) | 80 |
| Standard Operating Ambient Temperature | 25 |