
## **Glo-Ball Ceiling 1**


by Jasper Morrison , 1999



Ceiling mounted lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and of a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide ceiling fitting; gray painted die-cast aluminum diffuser support.







Mounting	Ceiling
Environment	Indoor
Finish	White
Weight	2.5 Kg
Light sources available	1 x MAX 150W E27 HSGS 2870lm 2900K [e] cod. RF20358 DIMMER 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 DIMMER
Emergency	Without
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes
Materials	Glass
Colors	F3023000 - White
Certificate	$C  C  \mathfrak{C}  \mathfrak{C}  C  C  \mathfrak{C}  $


## Glo-Ball Ceiling 2


by Jasper Morrison , 1999



Ceiling mounted lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and of a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide ceiling fitting; gray painted die-cast aluminum diffuser support.







Mounting	Ceiling
Environment	Indoor
Finish	White
Weight	5.1 Kg
Light sources available	1 x HSGS E27 205W 3000K Halolux Ceram.Eco 4200lm - RF19973 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 DIMMER
Emergency	Without
Voltage	220-250V
Power	MAX 250W
Battery	No
Supply included	Yes
Materials	Glass
Colors	F3028000 - White
Certificate	